

EAGLE-IP-PTZ-2MP-12

2MP 12X STARLIGHT IR PTZ



- 1/2.8" 2Megapixel STARVIS™ CMOS
- Powerful 12x optical zoom
- Starlight technology
- Max. 25/30fps@1080P
- IVS
- Support PoE+
- IR distance up to 100m
- IP66



System Overview

Featuring powerful optical zoom and accurate pan/tilt/zoom performance, the camera provides a wide monitoring range and great detail. The camera delivers 1080P resolution at 25/30fps. The camera is equipped with smooth control, high quality image, and good protection, meeting compact size demands of video surveillance applications.

Functions

Starlight Technology

For challenging low-light applications, Starlight Ultra-low Light Technology offers best-in-class light sensitivity, capturing color details in low light down to 0.005 lux. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

Wide Dynamic Range

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, True WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

Smart H.265+

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart H.265+ technology reduces bit rate and storage requirements by up to 70% when compared to standard H.265 video compression.

PFA Technology

PFA technology has innovatively introduced new methods of judgment to ensure the accuracy and predictability of the direction of subject distance adjustment. The result is a set of advanced focusing algorithms. PFA ensures clarity of the image throughout the process of zooming and shortens focus time. The realization of PFA technology substantially improves user experience and increases product value.

Environmental

The cameras operate in extreme temperature environments, rated for use in temperatures from -40 °C to +70 °C (-40 °F to +158 °F) with 95% humidity. Subjected to rigorous dust and water immersion tests and certified to the IP66 Ingress Protection rating makes it suitable for demanding outdoor applications.

Protection

The camera allows for 6KV lightning rating, which provides effective protection for both the camera and its structure against lightning.

Interoperability

The camera conforms to the ONVIF (Open Network Video Interface Forum) specifications, ensuring interoperability between network video products regardless of manufacturer.

Technical Specification				Advanced Intelligent Functions	Face Detection
Camera				Video	
Image Sensor	1/2.8" STARVIS™ CMOS			Compression	H.265+/H.265/H.264+/H.264
Effective Pixels	1920(H) x 1080(V), 2 Megapixels			Streaming Capability	3 Streams
RAM/ROM	1024M/128M			Resolution	1080P(1920×1080)/720P(1280×720)/D1(704×576/704×480)/CIF(352×288/352×240)
Scanning System	Progressive			Frame Rate	Main stream: 1080P/720P(1 ~ 25/30fps)
Electronic Shutter Speed	1/1s~1/30,000s				Sub stream1: D1/CIF(1 ~ 25/30fps)
Minimum Illumination	Color: 0.005Lux@F1.6; B/W: 0.0005Lux@F1.6; 0Lux@F1.6 (IR on)				Sub stream2: 720P/D1/CIF(1 ~ 25/30fps)
S/N Ratio	More than 50dB			Bit Rate Control	CBR/VBR
IR Distance	Distance up to 100m (328ft)			Bit Rate	H.265/H.264: 448K ~ 8192Kbps
IR On/Off Control	Auto/Manual			Day/Night	Auto(ICR) / Color / B/W
IR LEDs	6			Backlight Compensation	BLC / HLC / WDR(120dB)
Lens				White Balance	Auto, ATW, Indoor, Outdoor, Manual
Focal Length	5.3mm~64mm			Gain Control	Auto / Manual
Max. Aperture	F1.6 ~ F4.4			Noise Reduction	Ultra DNR (2D/3D)
Angle of View	H: 58.2° ~ 4.8°			Motion Detection	Support
Optical Zoom	12x			Region of Interest	Support
Focus Control	Auto/Manual			Electronic Image Stabilization (EIS)	N/A
Close Focus Distance	100mm~ 1000mm			Defog	Support
DORI Distance				Digital Zoom	16x
*Note: The DORI distance is a "general proximity" of distance which makes it easy to pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specification and lab test result according to EN 62676-4 which defines the criteria for Detect, Observe, Recognize and Identify respectively.					
Detect	Observe	Recognize	Identify	Flip	180°
883m(2897ft)	353m(1158ft)	177m(581ft)	88m(289ft)	Privacy Masking	Up to 24 areas
PTZ				Audio	
Pan/Tilt Range	Pan: 0° ~ 360° endless; Tilt: -15° ~ 90°, auto flip 180°			Compression	G.711a/G.711Mu/G.726/AAC
Manual Control Speed	Pan: 0.1° ~200° /s; Tilt: 0.1° ~120° /s			Network	
Preset Speed	Pan: 240° /s; Tilt: 200° /s			Ethernet	RJ-45 (10XBase-T/100Base-TX)
Presets	300			Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS,PPPOE,DDNS,FTP, IP Filter,QoS,Bonjour,802.1x
PTZ Mode	5 Pattern, 8 Tour, Auto Pan ,Auto Scan			Interoperability	ONVIF Profile S&G, API
Speed Setup	Human-oriented focal Length/ speed adaptation			Streaming Method	Unicast / Multicast
Power up Action	Auto restore to previous PTZ and lens status after power failure			Max. User Access	20 users
Idle Motion	Activate Preset/ Scan/ Tour/ Pattern if there is no command in the specified period			Edge Storage	NAS (Network Attached Storage),Local PC for instant recording, Micro SD card 256GB
Protocol	DH-SIP			Web Viewer	IE, Chrome, Firefox, Safari
Intelligence				Management Software	Smart PSS, DSS, DMSS
Event Trigger	Motion detection, Video tampering, Network disconnection, IP address conflict, Illegal access, Storage anomaly			Smart Phone	IOS, Android
Auto Tracking	N/A			Certifications	
IVS	Tripwire, Intrusion,Abandoned/Missing			Certifications	CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB,ANSI C63.4- 2014 UL: UL60950-1+CAN/CSA C22.2,No.60950-1

Interface

Video Interface	N/A
RS485	N/A
Audio I/O	1/1
Alarm I/O	2/1

Electrical

Power Supply	DC 12V/3A, PoE+(802.3at)
Power Consumption	13W, 22W (IR on, Heater on)

Environmental

Operating Conditions	-40°C ~ 70°C (-40°F ~ +158°F) / Less than 95% RH
Ingress Protection	IP66
Vandal Resistance	N/A

Construction

Casing	Metal
Dimensions	Φ160(mm) x 295(mm)
Net Weight	3kg(6.61lb)
Gross Weight	4.2kg(9.26lb)

Dimensions (mm)

